

EYELETING MACHINE: PRM22N-X2-AUTO



Specifically developed for setting eyelets on curtains (from Ø8 up to Ø40mm).

Machine comprised of 2 pneumatic presses:

- 1 on the right side, fixated, for piercing;
- 1 on the left side, on motorized rail, for eyeletting.

A computer calculates the number of eyelets needed relative to the curtain's size, and **automatically adjusts the spacing between both presses.**

Minimum spacing is 15cm, maximum 50cm.

A depth stop allows you to set the distance between the eyelets and the top of the curtain (max: 9cm).

The graduated ruler printed on the workplate will help the operator place the 1st eyelet.

Wheeled frame for easy displacement of the machine.

Cycle is triggered by a pedal, letting the operator stay **hands free** to manipulate the curtain.

Fast and easy dies set change (<2 min.)

Piercing is made by a "ball punch" like tool, **more efficient than bladed cutters.**

No hydraulic unit, rendering the machine **quieter**, and **saving maintenance costs.**

Complies with European safety standards **CE**

On request: Enhanced safety features: light signaling or two-handed control – Customization of the eyelet count calculation program – Stronger presses for round Ø50 and Ø65mm eyelets, and oval « TIR » eyelets.

TECHNICAL SPECS

Dimensions	135 x 65 x 134cm
Swan neck	110 mm
Weight	150 kg
Real cadence	300 eyelets / hour
Pneumatic supply	6 bars ; approx. 16L / cycle
Power supply	230Vac

1 year workshop return warranty: parts (excluding dies), and labor.

